## **Clinical Centrifuge 4500 rpm** CLC-02

**Usage** - the centrifuge is design to separate, sediment, spin down aqueous solutions and solvent suspensions of different sensitivity

**High-tech microprocessor** - Advanced microprocessor technology ensures dependable accuracy and precision with each spin cycle

**Intuitive user controls** - User-facing control panel provides quick access to all device features for quick and easy programming of the clinical centrifuge

**Maintenance-free DC motor** - Brushless DC motor with variable speeds provides reliable performance with minimum maintenance or downtime

**Combi rotor** - Convenient 8-slot rotor design fits 8 x 15 mL or 4 x 50 mL tubes at maximum capacity

**Excellent safety features** - Low noise, imbalance detection, and lid-lock safety mechanisms help to maintain an accidentfree laboratory environment

**Compact and portable** - Space-saving centrifuge design takes up a small amount of the workbench while a lightweight chassis makes it easy to move from one point to another

## **Ordering information**

Description	Cat. No.
myLab <sup>®</sup> CLC-02 Clinical Centrifuge 4500 rpm	7-011-00-0
Delivery Package	
1 pc. Clinical centrifuge 4500 rpm	
1 pc. 8-slots rotor (pre-installed)	
1 pc. Power supply adaptor	
1 pc. T-Allen Key	
4 pcs. 15 mL Reduction Adaptors	
8 pcs. Reduction adaptors and space	r
1 pc. Instruction manual	
1 pc. Warranty card	

Specifications	
Motor type	Brushless DC motor
Speed	500 to 4500 rpm
Speed accuracy	± 100 rpm
Max. volume	4 x 50 mL tubes
Timer setting	1 – 99 mins and infinity
Noise level	≤ 62 dB (A)
Weight	4 kg (with rotor)
Dimensions (WxDxH)	330x265x161 mm
Lid-lock	Yes
Imbalance detection	Yes







6

 $\bigcirc$